

Material Safety Data Sheet

and Safe Handling and Disposal Information

Section 1. Chemical Product and Company Identification

Product name ZEP STAINLESS STEEL POLISH
Product Use Aerosol Stainless Steel Cleaner and Polish

Product Code 0143

Date of issue 11/16/04 Supersedes 04/07/95

Emergency For MSDS Information:

Telephone Acuity Specialy Products Group, Inc.

Numbers Compliance Services 1-877-I-BUY-ZEP

For Medical Emergency:

INFOTRAC

(877) 541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency:

CHEMTREC

(800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

Prepared by Compliance Services Group

Acuity Specialty Products Group 1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Composition, Information on Ingredients

Name of Hazardous Ingredients	CAS#	% by Weight	Exposure Limits
PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate	64742-52-5	60 - 70	OSHA PEL (United States). : 5 mg/m³ 8 howr(s). Form: Mist ACGIH TLV (United States). : 5 mg/m³ 8 howr(s). Form: Mist
PETROLEUM SPIRITS; vm&p naphtha; refined solvent naphtha	8032-32-4	10 - 20	ACGIH (United States). TWA: 300 ppm OSHA (United States). STEL: 400 ppm
D-LIMONENE - orange distillate; citrus terpene; cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-	5989-27-5	5 - 10	
ISOPROPYL ALCOHOL; ipa; dimethylcarbinol; 2-propanol	67-63-0	<5	ACGIH TLV (United States). TWA: 200 ppm 8 hour(s). OSHA PEL (United States). TWA: 400 ppm 8 hour(s). ACGIH/OSHA (United States). STEL: 400 ppm 15 minute(s).

Section 3. Hazards Identification

Printing date: 11/16/04

Acute Effects Routes of Entry Absorbed through skin. Eye contact. Inhalation.

Skin Hazardous in case of skin contact (irritant, permeator, sensitizer). May cause allergic

reactions to certain individuals. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. Defatting properties, may aggravate an existing

dermatitis

Eyes Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by

redness, watering, and itching.

Inhalation Hazardous in case of inhalation. May cause respiratory tract irritation. Can cause central

nervous system depression. Medical Conditions Aggravated by Overexposure: Respiratory

Ingestion Unlikely in this form.

Carcinogenic Effects Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Chronic Effects Prolonged or repeated contact may dry skin and cause irritation. Over-exposure by inhalation or

absorption can cause central nervous system depression.

See Toxicological Information (section 11)

HMIS

HMIS	
Health	1
Fire Hazard	3
Reactivity	0
Personal Protection	В

Material Safety Data Sheet

Product Name ZEP STAINLESS STEEL POLISH

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical

attention.

Skin Contact Wash affected area with soap or mild detergent and water. Remove contaminated clothing and shoes. Get

medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Get medical attention.

Ingestion Aspiration hazard if swallowed- can enter lungs and cause damage. Do NOT induce vomiting unless

directed to do so by medical personnel. If vomiting occurs, keep head lower than hips to help prevent aspiration. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point Closed cup (Tagliabue.): <26°C Flammable Limits Not available.

(<79°F).

Flammability FLAMMABLE. (CSMA)

Fire Hazard FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Vapors may accumulate

in low or confined areas, travel considerable distance to source of ignition and flash back. Cool

closed containers exposed to fire with water.

Fire-Fighting Procedures Use dry chemical or CO₂. Wear special protective clothing and positive

pressure, self-contained breathing apparatus.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or

spray mists. Use only with adequate ventilation. Wash contaminated clothing before reusing.

Storage CONTENTS UNDER PRESSURE. Store and use away from heat, sparks, open flame, or any other ignition source.

Keep away from heat and direct sunlight. Keep container in a cool, well-ventilated area. Do not store above 49°C

(120.2°F). Do not puncture or incinerate. Keep out of the reach of children.

Section 8. Exposure Controls, Personal Protection

Personal Protection

Protective Clothing (Pictograms)

Eyes Safety glasses. **Body** Nitrile gloves.

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne

concentrations of vapors below their respective threshold limit value.

Section 9. Physical and Chemical Properties

Physical StateLiquid. (Aerosol.)Color Amber.pHNot applicable.Odor CitrusBoiling Point82.222°C (180°F)Vapor Pressure Not available.

Specific Gravity 0.856 (Water = 1) Vapor Pressure Not available.

Solubility Insoluble in cold water, hot water.

Vapor Pressure Not available.

Vapor Density Not available.

Evaporation Rate Not available.

VOC (Consumer) 24.8% 1.77 lbs/gal 212 g/l

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Avoid contact with strong oxidizers, excessive heat, sparks or open flame. Incompatible with some

alkalis.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products Carbon Dioxide, Carbon Monoxide and other organic materials...

Section 11. Toxicological Information

Toxicity to Animals Petroleum spirits:

VAPOR (LC50): Acute: 3400 ppm 4 hour(s) [Rat].

d-Limonene:

ORAL (LD50): Acute: 5600 mg/kg [Mouse]. 4400 mg/kg [Rat].

DERMAL (LD50): Acute: >5000 mg/kg [Rabbit].

Isopropyl Alcohol:

ORAL (LD50): Acute: 4700 mg/kg [Rat].
DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].

VAPOR (LC50): Acute: 22500 ppm 8 hour(s) [Rat (Male)]. 19000 ppm 8 hour(s) [Rat

(Female)].

Product Code 0143 Material Safety Data Sheet Product Name ZEP STAINLESS STEEL POLISH

Section 12. Ecological Information

Ecotoxicity Not available. **Biodegradable/OECD** Not available.

Section 13. Disposal Considerations

Waste Maste Maste must be disposed of in accordance with federal, Waste Stream Code: D001

Information state and local environmental control regulations. Classification: - (Hazardous waste.)

Origin: - (RCRA waste.)

Consult your local or regional authorities.

Section 14. Transport Information

Proper shipping name Consumer Commodity

DOT Classification ORM-D **UN number** Not regulated.

Section 15. Regulatory Information

U.S. Federal Regulations SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.